

10dB Leistungsdämpfungsglied

-10,0 dB	Ohm	Watt	Volt	Ampere
TRX	50,00	10,00	22,36	0,45

	Ohm	Watt	Volt	Ampere	#R	R	Watt
R1	96,25	5,19	22,36	0,23			
R1a	109,09	4,58	22,36		11	1200	0,42
R1b	820,00	0,61	22,36		1	820	0,61
R1'	96,28	5,19	22,36				

	Ohm	Watt	Volt	Ampere	#R	R	Watt
R2	71,15	3,29	15,29	0,21			
R2a	78,00	3,00	15,29		5	390	0,60
R2b	820,00	0,29	15,29		1	820	0,29
R2'	71,22	3,28	15,29				

	Ohm	Watt	Volt	Ampere	#R	R	Watt
R3	96,25	0,52	7,07	0,07			
R3a	195,00	0,26	7,07		2	390	0,13
R3b	235,00	0,21	7,07		2	470	0,11
R3c	1000,00	0,05	7,07		1	1000	0,05
R3'	96,31	0,52	7,07				

	Ohm	Watt	Volt	Ampere
R50	50,00	1,00	7,07	0,14

R3*	32,91	1,52	7,07	0,21
R2*	104,06	4,81	22,36	0,21
R1*	50,00	10,00	22,36	0,45